

# Asphalt blender

**Tare**

✓ Rock, gravel and heat

**Function**

✓ Side plates for mixing

**Processing**

✓ Plasma cutting  
✓ Bending and welding

**Comparative tests**



**Peab Asphalt**

Comparative solutions	Compereson against 9 months of operation
HB450, Thickness 8mm, Fraktion 0-16	50.000 Ton / 9 months = 5556 Ton / months
<b>CREUSABRO® 8000®</b> Thickness 8mm, Fraktion 8-16	70.000 Ton / 9 months = 7778 Ton / months

**CREUSABRO® 8000®**  
**+40%**

**BERGS**  
**MEKANISKA**

# Asphalt blender

The test did not take into account the fraction difference that was between the different sheet qualities.

In tests with **CREUSABRO® 8000®** we used fractions 8-16 and at HB450 the quality was driven fraction 0-16.

It is demonstrated by testing that **CREUSABRO® 8000®** has a higher strength in used fractions than the HB450.

For **CREUSABRO® 8000®**, this is a good application when it can handle up to 450 ° C.

The customer estimates that on a test of the same fraction, the strength of **CREUSABRO® 8000®** been significantly higher than the test demonstrated now.



**PEAB**

**Peab Asphalt**

**BERGS  
MEKANISKA**

Compared solutions	Fractions
HB450, 8mm 150-200°C	0-16
CREUSABRO® 8000, 8mm 150-200°C	8-16

**CREUSABRO® 8000®**  
**+40%**